

BRINEMASTERS" CONTINUUM TF-XR

Truck Fill Station with Real-Time Blending & Variable Flow Rates



LIQUID DEICES

Brine MastersTM ContinuumTM TF-XR Truck Fill Station is a real-time blending system with variable flow rates. Blend up to 3 products at ratios between 1% and 50%. Simplifies user interface, password protection, data logging and built-in diagnostics are all standard. This unit can be installed inside or outside. Compatible with any brand of brine system.







Controls	
BlendingType	Real-Time with Variable Flow Rate
Fully Automated Blend & Truck Fill	Yes
Number of Products to Blend	Up to 3
Flow Rates	Variable 50 - 300 GPM
Maximum Number of Fill Points	3
User Interface	10" Color Touch Screen & Push Button / Outdoor-Rated / Ultra Bright
Data Logging	Yes
Data Download	USB or Internet
Built-In Self Diagnostics	Yes
Cellular Remote Access	Yes
System Expandible	Yes
Controls Cabinet Weather-Proofing	NEMA 4X
UL Listed	Yes

Mechanical	
Flow Rates	Variable 50 - 300 GPM
Overall Dimensions	69" x 39" x 76"H
Frame Construction	10-Gauge 304 Stainless Steel
Flow Meter	Electronic MAG Meter
Valve Type	Electric Proportional
Pump Design	Close-Coupled / Centrifugal
Pump Construction	Cast Stainless Steel
Pump Motor Design	Washdown rated / Inverter Ready
Pump Motor Construction	Stainless Steel
Pump Motor Rating	5 HP, 7.5 HP, or 10 HP
Pump Motor Drive	Variable Speed
Pump Motor Voltage/Phase	Single Phase or Three Phase

Options	
Storage Tank Level Monitoring	Micro Ingredient Capability: Up to 2
Air Purge	Built-in Toolbox

Product specifications subject to change due to continuous improvement practices.



(800) 735-1881 sales@norstarind.com