



BRINEMASTERS™ CONTINUUM™ TF-XS

Truck Fill Station with Stack Blending & Variable Flow Rates



Brine Masters™ Continuum™ TF-XS Truck Fill Station is a stack blending system with variable flow rates. Blend up to 3 products at ratios between 1% and 50%. Simplifies user interface, password protection, data logging and built-in diagnostics are all standard. This unit can be installed inside or outside. Compatible with any brand of brine system.



**Intuitive
Operation**



Secure



Durable

Controls

Blending Type	Stack with Variable Flow Rate
Fully Automated Blend & Truck Fill	Yes
Number of Products to Blend	Up to 3
Flow Rates	Variable 50 - 300 GPM
Maximum Number of Fill Points	Unlimited
User Interface	7" Color Touch Screen & Push Button/ Outdoor-Rated/Ultra Bright
Data Logging	Yes
Data Download	USB or Internet
Built-In Self Diagnostics	Yes
Cellular Remote Access	Yes
System Expandable	Yes
Controls Cabinet Weather-Proofing	NEMA 4X
UL Listed	Yes

Mechanical

Flow Rates	Variable 20 - 300 GPM
Overall Dimensions	69" x 39" x 76"H
Frame Construction	10-Gauge 304 Stainless Steel
Flow Meter	Electronic MAG Meter
Valve Type	Electric On / Off
Pump Design	Close-Coupled / Centrifugal
Pump Construction	Cast Stainless Steel
Pump Motor Design	Washdown rated / Inverter Ready
Pump Motor Construction	Stainless Steel
Pump Motor Rating	5 HP, 7.5 HP, or 10 HP
Pump Motor Drive	Variable Speed
Pump System	Single Phase 220V or Three Phase 208V

Options

Storage Tank Level Monitoring	Micro Ingredient Capability
Air Purge	Built-in Toolbox

Product specifications subject to change due to continuous improvement practices.

NORSTAR®
INDUSTRIES, INC.

(800) 735-1881
sales@norstarind.com
norstarind.com